Product datasheet

Specifications

Sreen Premium[™]



LINERGY FM 4P DIST.BLOCK 63A 12M 20HOLES

04008

() Discontinued on: Jan 11, 2022 AD

① Discontinued

Main

Range	Linergy
Range Of Product	Linergy
Product Or Component Type	Device feeder
Product Name	Linergy FM
Range Compatibility	Prisma Prisma G enclosure Prisma Prisma P enclosure Prisma Prisma PH enclosure Prisma Prisma Pack 250 enclosure
Product Compatibility	Spacial enclosures
Ip Degree Of Protection	IPxx B

Complementary

Mounting Support	DIN rail Slotted backplate Plain backplate
Installed Device	modular device
Poles Description	3P + N
[Ue] Rated Operational Voltage	440 V AC
[Ui] Rated Insulation Voltage	500 V AC 50/60 Hz
[Uimp] Rated Impulse Withstand Voltage	6 kV
[Ie] Rated Operational Current	63 A
[In] Rated Current	63 A at 40 °C
[Ipk] Rated Peak Withstand Current	12 kA
I ² T On Activation	2400000 A².s
Connections - Terminals	Supply: tunnel type terminal25 mm ² Distribution: quick-connect terminal strips (phase) , 2 x 46 mm ² (rigid) Distribution: quick-connect terminal strips (phase) , 2 x 46 mm ² (flexible) Distribution: quick-connect terminal strips (neutral) , 4 x 46 mm ² (rigid) Distribution: quick-connect terminal strips (neutral) , 4 x 46 mm ² (flexible) Distribution: quick-connect terminal strips (phase) , 2 x 1.54 mm ² (flexible) Distribution: quick-connect terminal strips (phase) , 2 x 1.54 mm ² (flexible) Distribution: quick-connect terminal strips (phase) , 2 x 1.54 mm ² (flexible) Distribution: quick-connect terminal strips (neutral) , 4 x 1.54 mm ² (flexible)
9 Mm Pitches	24
Total Number Of 18 Mm Modules	12
Net Weight	0.46 kg

Colour

Anthracite grey (RAL 7016)

Environment

Standards	IEC 61439-1, inside Prisma IEC 61439-2, inside Prisma IEC 60947-7-1
Product Certifications	ASEFA

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.6 cm
Package 1 Width	6.2 cm
Package 1 Length	23.2 cm
Package 1 Weight	450 g

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes
Halogen Free Product

Certifications & Standards

Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins