

Product datasheet

Specifications



Linergy DX 4P distribution block 63A - 4 modules - 24 holes quick connect bottom

04041

⚠ Discontinued on: Dec 31, 2021 AD

⚠ Discontinued

Main

| | |
|---------------------------|---|
| Range | Linergy |
| Range Of Product | Prisma Plus System P Prisma Plus System G |
| Product Or Component Type | Distribution block |
| Product Name | Linergy DX |
| Range Compatibility | Prisma Prisma G Prisma Prisma P Prisma Prisma PH Prisma Pack 160 Prisma Prisma Pack 250 |
| Product Compatibility | Spacial enclosures |
| Ip Degree Of Protection | IPxx B |

Complementary

| | |
|--|---|
| Location Of Connection | Bottom |
| Mounting Support | DIN rail |
| Poles Description | 4P |
| [Ue] Rated Operational Voltage | 440 V AC |
| [Ui] Rated Insulation Voltage | 500 V AC |
| [Uimp] Rated Impulse Withstand Voltage | 6 kV |
| [Ie] Rated Operational Current | 63 A at 40 °C |
| [In] Rated Current | 63 A at 40 °C |
| Connections - Terminals | Supply: tunnel type terminal16 mm² (flexible) Supply: tunnel type terminal25 mm² (rigid) Distribution: spring terminal (phase) , 12 x 2.5...6 mm² (flexible) Distribution: spring terminal (phase) , 12 x 2.5...6 mm² (rigid) Distribution: spring terminal (neutral) , 12 x 2.5...6 mm² (flexible) Distribution: spring terminal (neutral) , 12 x 2.5...6 mm² (rigid) |
| 9 Mm Pitches | 8 |
| Total Number Of 18 Mm Modules | 4 |
| Net Weight | 0.29 kg |

Environment

| | |
|---------------------------------|-------------------------------------|
| Pollution Degree | 3 |
| Resistance To Incandescent Wire | 960 °C conforming to IEC 60695-2-11 |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|------------------------|---------------|
| Standards | IEC 60947-7-1 |
| | IEC 61439-2 |
| | IEC 61439-1 |
| Product Certifications | ASEFA |

Packing Units

| | |
|------------------------------|---------|
| Unit Type Of Package 1 | PCE |
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 7.6 cm |
| Package 1 Width | 8 cm |
| Package 1 Length | 10.4 cm |
| Package 1 Weight | 316 g |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Sustainability





Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

| | |
|--|---|
|  Reach Free Of Svhc | |
|  Toxic Heavy Metal Free | |
|  Mercury Free | |
|  Rohs Exemption Information | Yes |
| Reach Regulation | REACH Declaration |
| Eu Rohs Directive | Compliant EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |