


INSULATED FLEX.BAR 32X5 L1800

04751

! Discontinued on: Oct 29, 2021 AD



Main

Range	Prisma	
Range Of Product	Prisma G	
	Prisma P	
Product Or Component Type	Insulated flexible bar	
Product Name	Prisma Prisma G enclosure	
	Prisma Prisma P enclosure	
	Prisma Prisma iPM L enclosure	
	Prisma Prisma iPM M enclosure	
Accessory / Separate Part Category	Part Current distribution accessory	
Standards	IEC 61439-2	
	IEC 61439-1	
Product Certifications	ASEFA	

Complementary

Installation Description	Cubicle Floor-standing enclosure Wall-mounted enclosure	
[le] Rated Operational Current	520 A	
[In] Rated Current	520 A	
Busbar Cross Section	32 x 5 mm	
Length	1800 mm	
Net Weight	3.38 kg	
Quantity Per Set	Set of 1	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2 cm
Package 1 Width	11 cm
Package 1 Length	192 cm
Package 1 Weight	3.250 kg



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

Ø	Reach Free Of Svhc	
Ø	Toxic Heavy Metal Free	
9	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile