



# Interface enclosure, Mureva Enclosure, 4 openings 90x100mm, (W) 138mm x (H) 610mm

13994

### Main

| Range                      | Mureva                 |
|----------------------------|------------------------|
| Product Name               | Mureva Enclosure       |
| Product Or Component Type  | Weatherproof enclosure |
| Enclosure Type             | Interface enclosure    |
| Mounting Plate Description | Without mounting plate |

## Complementary

| Enclosure Mounting              | Surface   |
|---------------------------------|---|
| Electrical Insulation Class     | Class II<br>Double insulation                                       |
| Number Of Openings Of Interface | 4   |
| Number Of Plates                | 1 for 65 x 85 power outlets 4 for push-button controls              |
| Provided Equipment              | 1 plate for 65 x 85 power outlet<br>4 plate for push-button control |
| Type Of Front Cover             | Opaque  |
| Number Of Pre-Cutouts Pg Iso    | 3   |
| Enclosure Material              | Self-extinguishing polymer  |
| Base Dimension                  | 90 x 100 mm   |
| Width                           | 138 mm  |
| Height                          | 610 mm  |
| Depth                           | 160 mm  |
| Internal Depth                  | 88 mm   |
| Colour                          | Enclosure: light grey (RAL 7035)                                    |

### **Environment**

| Standards                          | EN 50262<br>IEC 60670<br>IEC 61439-3<br>IEC 60695-2-1  |
|------------------------------------|--|
| Fire Resistance                    | 650 °C conforming to IEC 60695-2-1   |
| Ip Degree Of Protection            | IP65 conforming to IEC 60529   |
| Ik Degree Of Protection            | IK09 conforming to EN 50102  |
| Environmental Characteristics (Uv) | UV resistant: class 3 conforming to ISO 4582:2010 Ultraviolet degradation test conforming to ISO 4892-2:2013 |

| Overvoltage Category                  | II       |
|---------------------------------------|----------|
| Ambient Air Temperature For Operation | -2560 °C |

## **Packing Units**

| Unit Type Of Package 1       | PCE       |
|------------------------------|-----------|
| Number Of Units In Package 1 | 1         |
| Package 1 Height             | 13.5 cm   |
| Package 1 Width              | 15.8 cm   |
| Package 1 Length             | 62.0 cm   |
| Package 1 Weight             | 1.595 kg  |
| Unit Type Of Package 2       | P12       |
| Number Of Units In Package 2 | 64        |
| Package 2 Height             | 80.0 cm   |
| Package 2 Width              | 80.0 cm   |
| Package 2 Length             | 120.0 cm  |
| Package 2 Weight             | 114.08 kg |

## **Contractual warranty**

Warranty 18 months



Green Premium<sup>TM</sup> label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >








Lower Impact Materials Transparency RoHS/REACh

### Resource performance



#### Well-being performance

Rohs Exemption Information



#### **Certifications & Standards**

| Reach Regulation         | REACh Declaration   |
|--------------------------|---|
| Eu Rohs Directive        | Pro-active compliance (Product out of EU RoHS legal scope)  |
| China Rohs Regulation    | China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile   |
| Circularity Profile      | No need of specific recycling operations  |