Product datasheet

Specification





Socket, Vivace, universal, 3pin, 13A, 250V, 1 gang, white

KB413S

Main

| Range | Vivace | |
|---------------------------|--------------------|--|
| Product Or Component Type | Socket-outlet | |
| Device Short Name | KB426 | |
| Device Application | Power supply | |
| Device Presentation | Complete mechanism | |
| Outlet Standard | Universal | |
| Colour Tint | White | |
| Type Of Packing | Plastic bag | |
| Socket Number | 1 | |
| Rated Current | 13 A | |
| Colour Tint | Wall: white | |

Complementary

| Integrated Connection Type | 1 socket-outlet 220250 V AC, maximum load current: 13 A | |
|--------------------------------|---|--|
| Outlet Standard | Universal | |
| Outlet Poles Configuration | 2P + E with shutter | |
| Number Of Gangs | 1 gang | |
| Material | Polycarbonate: grid plate Polycarbonate: surround Nylon: base | |
| Projecting Depth | 8 mm | |
| Device Mounting | Flush | |
| Mounting Support | Wall mounted | |
| Fixing Mode | By screws | |
| Fixing Center | 60.3 mm | |
| Embedding Depth | 25 mm | |
| Rated Current | 13 A at 250 V AC, resistive | |
| [Ue] Rated Operational Voltage | 220240 V | |
| Network Frequency | 50/60 Hz | |
| Network Type | AC | |
| Contacts Material | Brass and phosphor bronze | |
| Connections - Terminals | Screw terminals | |

| Terminal Identifier | 1 |
|------------------------------|---|
| Terminar Identifier | L |
| | N |
| | E |
| Tightening Torque | 0.4 N.m |
| Clamping Connection Capacity | 2.5 mm² 4 mm² |
| | 7 (11) |
| Width | 86 mm |
| Surface Treatment | Untreated |
| Height | 86 mm |
| Surface Finish | Glossy |
| Depth | 33 mm |
| Number Of Terminals | 3 |
| Clamping Connection Capacity | 1 x 2.53 x 2.5 mm² for rigid or stranded cable(s) |

Environment

| Ambient Air Temperature For Operation | -540 °C |
|---------------------------------------|------------|
| Ambient Air Temperature For Storage | -560 °C |
| Relative Humidity | 095 % |
| Operating Altitude | 02000 m |
| Environmental Characteristic | Indoor use |
| Ip Degree Of Protection | IP20 |

Packing Units

| PCE |
|----------|
| 1 |
| 8.6 cm |
| 3 cm |
| 8.6 cm |
| 108.6 g |
| BB1 |
| 10 |
| 15 cm |
| 19 cm |
| 10 cm |
| 1.156 kg |
| CAR |
| 100 |
| 21 cm |
| 31.5 cm |
| 50 cm |
| 11108 g |
| |

Contractual warranty

Warranty

18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

| ⊘ | Reach Free Of Svhc | |
|----------|----------------------------|-----|
| ⊘ | Toxic Heavy Metal Free | |
| ⊘ | Mercury Free | |
| ⊘ | Rohs Exemption Information | Yes |

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|---|
| Eu Rohs Directive | Compliant EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |