Product datasheet

Specifications





Contactor, TeSys Deca, 3P(3NO), AC-3/AC-3e, 440V, 80A, 230V AC 50/60Hz coil, screw clamp terminals

LC1D80P7

Main

Range	TeSys	
Range Of Product	TeSys Deca	
Product Or Component Type	Contactor	
Device Short Name	LC1D	
Contactor Application	Resistive load Motor control	
Utilisation Category	AC-3 AC-3e AC-4 AC-1	
Poles Description	3P	
[Ue] Rated Operational Voltage	Power circuit: <= 300 V DC 25400 Hz Power circuit: <= 690 V AC	
[le] Rated Operational Current	125 A (at <60 °C) at <= 440 V AC AC-1 for power circuit 80 A (at <60 °C) at <= 440 V AC AC-3 for power circuit 80 A (at <60 °C) at <= 440 V AC AC-3e for power circuit	
[Uc] Control Circuit Voltage	230 V AC 50/60 Hz	

Complementary

Motor Power Kw	22 kW at 220230 V AC 50 Hz (AC-3)	
	37 kW at 380400 V AC 50 Hz (AC-3)	
	45 kW at 415440 V AC 50 Hz (AC-3)	
	55 kW at 500 V AC 50 Hz (AC-3)	
	45 kW at 660690 V AC 50 Hz (AC-3)	
	15 kW at 400 V AC 50 Hz (AC-4)	
	22 kW at 220230 V AC 50/60 Hz (AC-3e)	
	37 kW at 380400 V AC 50/60 Hz (AC-3e)	
	45 kW at 415440 V AC 50/60 Hz (AC-3e)	
	55 kW at 500 V AC 50/60 Hz (AC-3e)	
	45 kW at 660690 V AC 50/60 Hz (AC-3e)	
Motor Power Hp	7.5 hp at 120 V AC 50/60 Hz for 1 phase motors	
	15 hp at 230/240 V AC 50/60 Hz for 1 phase motors	
	30 hp at 200/208 V AC 50/60 Hz for 3 phases motors	
	30 hp at 230/240 V AC 50/60 Hz for 3 phases motors	
	60 hp at 460/480 V AC 50/60 Hz for 3 phases motors	
	60 hp at 575/600 V AC 50/60 Hz for 3 phases motors	
Compatibility Code	LC1D	
Pole Contact Composition	3 NO	
Protective Cover	With	
[Ith] Conventional Free Air	10 A (at 60 °C) for signalling circuit	
Thermal Current	125 A (at 60 °C) for power circuit	
Irms Rated Making Capacity	140 A AC for signalling circuit conforming to IEC 60947-5-1	
	250 A DC for signalling circuit conforming to IEC 60947-5-1	
	1100 A at 440 V for power circuit conforming to IEC 60947	

Rated Breaking Capacity	1100 A at 440 V for power circuit conforming to IEC 60947
[Icw] Rated Short-Time Withstand Current	640 A 40 °C - 10 s for power circuit 990 A 40 °C - 1 s for power circuit 135 A 40 °C - 10 min for power circuit 320 A 40 °C - 1 min for power circuit 100 A - 1 s for signalling circuit 120 A - 500 ms for signalling circuit 140 A - 100 ms for signalling circuit
Associated Fuse Rating	10 A gG for signalling circuit conforming to IEC 60947-5-1 200 A gG at <= 690 V coordination type 1 for power circuit 160 A gG at <= 690 V coordination type 2 for power circuit
Average Impedance	0.8 mOhm - Ith 125 A 50 Hz for power circuit
Power Dissipation Per Pole	5.1 W AC-3 12.5 W AC-1 5.1 W AC-3e
[Ui] Rated Insulation Voltage	Power circuit: 600 V CSA certified Power circuit: 600 V UL certified Power circuit: 1000 V conforming to IEC 60947-4-1 Signalling circuit: 690 V conforming to IEC 60947-1 Signalling circuit: 600 V CSA certified Signalling circuit: 600 V UL certified
Overvoltage Category	III
Pollution Degree	3
[Uimp] Rated Impulse Withstand Voltage	8 kV conforming to IEC 60947
Safety Reliability Level	B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1
Mechanical Durability	4 Mcycles
Electrical Durability	0.8 Mcycles 125 A AC-1 at Ue <= 440 V 1.5 Mcycles 80 A AC-3 at Ue <= 440 V 1.5 Mcycles 80 A AC-3e at Ue <= 440 V
Control Circuit Type	AC at 50/60 Hz standard
Coil Technology	Without built-in suppressor module
Control Circuit Voltage Limits	0.851.1 Uc (-4055 °C):operational AC 60 Hz 0.30.6 Uc (-4070 °C):drop-out AC 50/60 Hz 0.81.1 Uc (-4055 °C):operational AC 50 Hz 11.1 Uc (5570 °C):operational AC 50/60 Hz
Inrush Power In Va	245 VA 60 Hz cos phi 0.75 (at 20 °C) 245 VA 50 Hz cos phi 0.75 (at 20 °C)
Hold-In Power Consumption In Va	26 VA 60 Hz cos phi 0.3 (at 20 °C) 26 VA 50 Hz cos phi 0.3 (at 20 °C)
Heat Dissipation	610 W at 50/60 Hz
Operating Time	2035 ms closing 620 ms opening
Maximum Operating Rate	3600 cyc/h 60 °C

Ip Degree Of Protection	IP20 front face conforming to IEC 60529
	CSA UL
	RINA BV
	GL
	GOST CCC
	LROS (Lloyds register of shipping)
Product Certifications	DNV
	UL 508
	IEC 60947-5-1
	EN 60947-5-1 IEC 60947-4-1
	EN 60947-4-1 EN 60947-5-1
Standards	CSA C22.2 No 14
Environment	
	. 1000
Mounting Support	Rail Plate
	1.5 ms on energisation between NC and NO contact
Non-Overlap Time	1.5 ms on de-energisation between NC and NO contact
Insulation Resistance	> 10 MOhm for signalling circuit
Minimum Switching Current	5 mA for signalling circuit
Minimum Switching Voltage	17 V for signalling circuit
Signalling Circuit Frequency	25400 Hz
Auxiliary Contacts Type	type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1 type mirror contact 1 NC conforming to IEC 60947-4-1
Auxiliary Contact Composition	1 NO + 1 NC
	Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver Philips No 2 Power circuit: 12 N.m - on connector - with screwdriver flat Ø 6 to Ø 8 mm Power circuit: 12 N.m - on connector hexagonal screw head 4 mm Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver pozidriv No 2
Tightening Torque	Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm
	Power circuit: connector 1 450 mm² - cable stiffness: solid without cable end Power circuit: connector 2 425 mm² - cable stiffness: solid without cable end
	Power circuit: connector 2 416 mm² - cable stiffness: flexible with cable end
	Power circuit: connector 2 425 mm² - cable stiffness: flexible without cable end Power circuit: connector 1 450 mm² - cable stiffness: flexible with cable end
	Power circuit: connector 1 450 mm² - cable stiffness: flexible without cable end
	Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: solid without cable end
	cable end
	cable end Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: solid without
	cable end Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: flexible without
	Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible without
	Control circuit: screw clamp terminals 1 12.5 mm² - cable stiffness: flexible with cable end
	cable end

Protective Treatment TH conforming to IEC 60068-2-30 Climatic Withstand conforming to IACS E10 exposure to damp heat Permissible Ambient Air Temperature Around The Device 60...70 °C with derating Operating Altitude 0...3000 m Fire Resistance 850 °C conforming to IEC 60695-2-1 Flame Retardance V1 conforming to UL 94

Mechanical Robustness	Vibrations contactor open (2 Gn, 5300 Hz) Shocks contactor open (8 Gn for 11 ms) Vibrations contactor closed (3 Gn, 5300 Hz) Shocks contactor closed (10 Gn for 11 ms)	
Height	127 mm	
Width	85 mm	
Depth	130 mm	
Net Weight	1.59 kg	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	9.500 cm
Package 1 Width	13.500 cm
Package 1 Length	14.000 cm
Package 1 Weight	1.566 kg
Unit Type Of Package 2	S02
Number Of Units In Package 2	5
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	8.059 kg
Unit Type Of Package 3	P06
Number Of Units In Package 3	80
Package 3 Height	75.000 cm
Package 3 Width	80.000 cm
Package 3 Length	60.000 cm
Package 3 Weight	136.944 kg

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance


⊘	Reach Free Of Svhc
⊘	Toxic Heavy Metal Free
⊘	Mercury Free
⊘	Rohs Exemption Information Yes
②	Pvc Free

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations

Dimensions Drawings

Dimensions



(1) Minimum electrical clearance

LC1 D80 D95 a 85 85 with LA4 D●2 135 135 with LA4 DB3 or LAD 4BB3 135 - with LA4 DF, DT 142 142 with LA4 DM, DW, DL 150 150 c without cover or add-on blocks 125 125 with cover, without add-on blocks 130 130 c1 with LAD N (1 contact) 150 150 with LAD N or C (2 or 4 contacts) 158 158 c2 with LA6 DK10, LAD 6DK 170 170 with LAD T, R, S 178 178 with LAD T, R, S and sealing cover 182 182				
with LA4 D●2 135 135 b1 with LA4 DB3 or LAD 4BB3 135 − with LA4 DF, DT 142 142 with LA4 DM, DW, DL 150 150 without cover or add-on blocks 125 125 with cover, without add-on blocks 130 130 c1 with LAD N (1 contact) 150 150 with LAD N or C (2 or 4 contacts) 158 158 c2 with LA6 DK10, LAD 6DK 170 170 with LAD T, R, S 178 178	LC1	C1		D95
b1 with LA4 DB3 or LAD 4BB3 135 - with LA4 DF, DT 142 142 with LA4 DM, DW, DL 150 150 c without cover or add-on blocks 125 125 with cover, without add-on blocks 130 130 c1 with LAD N (1 contact) 150 150 with LAD N or C (2 or 4 contacts) 158 158 c2 with LA6 DK10, LAD 6DK 170 170 with LAD T, R, S 178 178 178	а		85	85
b1 with LA4 DF, DT 142 142 with LA4 DM, DW, DL 150 150 without cover or add-on blocks 125 125 with cover, without add-on blocks 130 130 with LAD N (1 contact) 150 150 with LAD N or C (2 or 4 contacts) 158 158 c2 with LA6 DK10, LAD 6DK 170 170 with LAD T, R, S 178 178		with LA4 D●2	135	135
with LA4 DF, DT 142 142 with LA4 DM, DW, DL 150 150 without cover or add-on blocks 125 125 with cover, without add-on blocks 130 130 with LAD N (1 contact) 150 150 with LAD N or C (2 or 4 contacts) 158 158 c2 with LA6 DK10, LAD 6DK 170 170 with LAD T, R, S 178 178		with LA4 DB3 or LAD 4BB3	135	_
c without cover or add-on blocks 125 125 with cover, without add-on blocks 130 130 c1 with LAD N (1 contact) 150 150 with LAD N or C (2 or 4 contacts) 158 158 c2 with LA6 DK10, LAD 6DK 170 170 with LAD T, R, S 178 178	ומן	with LA4 DF, DT	142	142
c with cover, without add-on blocks 130 130 with LAD N (1 contact) 150 150 with LAD N or C (2 or 4 contacts) 158 158 c2 with LA6 DK10, LAD 6DK 170 170 with LAD T, R, S 178 178 c3		with LA4 DM, DW, DL	150	150
with cover, without add-on blocks 130 130 with LAD N (1 contact) 150 150 with LAD N or C (2 or 4 contacts) 158 158 c2 with LA6 DK10, LAD 6DK 170 170 with LAD T, R, S 178 178		without cover or add-on blocks	125	125
c1 with LAD N or C (2 or 4 contacts) 158 158 c2 with LA6 DK10, LAD 6DK 170 170 with LAD T, R, S 178 178	С	with cover, without add-on blocks	130	130
with LAD N or C (2 or 4 contacts) 158 158 c2 with LA6 DK10, LAD 6DK 170 170 with LAD T, R, S 178 178		with LAD N (1 contact)	150	150
with LAD T, R, S 178 178	CT	with LAD N or C (2 or 4 contacts)	158	158
c3	c2	with LA6 DK10, LAD 6DK	170	170
	-2	with LAD T, R, S	178	178
	c3	with LAD T, R, S and sealing cover	182	182

Connections and Schema

Wiring

