Product datasheet

Specifications





Contactor,Easy TeSys Control,LC1E, 3P(3NO),AC-3,<=440V,12A,24V AC coil,50Hz,1NC auxiliary contact

LC1E1201B5

Main

Range	Easy TeSys	
Range Of Product	Easy TeSys Control	
Product Or Component Type	Contactor	
Device Short Name	LC1E	
Contactor Application	Resistive load Motor control	
Utilisation Category	AC-3 AC-1	
Poles Description	3P	
[Ue] Rated Operational Voltage	Power circuit: <= 690 V AC 50/60 Hz	
[le] Rated Operational Current	25 A (at <55 °C) at <= 440 V AC AC-1 for power circuit 12 A (at <55 °C) at <= 440 V AC AC-3 for power circuit	
[Uc] Control Circuit Voltage	24 V AC 50 Hz	

Complementary

Motor Power Kw	3 kW at 220230 V AC 50/60 Hz (AC-3)
	5.5 kW at 380400 V AC 50/60 Hz (AC-3)
	5.5 kW at 415 V AC 50/60 Hz (AC-3)
	5.5 kW at 440 V AC 50/60 Hz (AC-3)
	7.5 kW at 500 V AC 50/60 Hz (AC-3)
	7.5 kW at 660690 V AC 50/60 Hz (AC-3)
Pole Contact Composition	3 NO
[Ith] Conventional Free Air Thermal Current	25 A (at 55 °C) for power circuit
Irms Rated Making Capacity	120 A at 440 V AC for power circuit conforming to IEC 60947-4-1
Rated Breaking Capacity	96 A at 440 V for power circuit conforming to IEC 60947
[Icw] Rated Short-Time Withstand	105 A 40 °C - 10 s for power circuit
Current	61 A 40 °C - 60 s for power circuit
	30 A 40 °C - 600 s for power circuit
Associated Fuse Rating	10 A gG at <= 690 V coordination type 1 for control circuit conforming to IEC
	60947-5-1
	25 A gG at <= 690 V coordination type 1 for power circuit
Average Impedance	2.5 mOhm - Ith 25 A 50 Hz for power circuit
Power Dissipation Per Pole	0.36 W AC-3
	1.6 W AC-1
[Ui] Rated Insulation Voltage	690 V conforming to IEC 60947-4-1
Overvoltage Category	III
Pollution Degree	3

[Uimp] Rated Impulse Withstand Voltage	6 kV coil not connected to the power circuit conforming to IEC 60947
Mechanical Durability	1000000 cycles
Electrical Durability	1400000 cycles AC-3 300000 cycles AC-1
Control Circuit Type	AC at 50 Hz
Control Circuit Voltage Limits	0.851.1 Uc (-555 °C):operational 50 Hz
	0.30.6 Uc (-555 °C):drop-out 50 Hz
Inrush Power In Va	95 VA 50 Hz cos phi 0.75 (at 20 °C)
	95 VA 60 Hz cos phi 0.75 (at 20 °C)
Hold-In Power Consumption In Va	8.3 VA 50 Hz cos phi 0.3 (at 20 °C) 8.5 VA 60 Hz cos phi 0.3 (at 20 °C)
Heat Dissipation	23 W for control circuit
Operating Time	1222 ms on closing
	419 ms on opening
Maximum Operating Rate	1800 cyc/h 60 °C
Connections - Terminals	Power circuit: screw clamp terminals 1 14 mm ² - cable stiffness: flexible with cable
	end Power circuit: screw clamp terminals 2.1 2.5 mm ² - cable stiffness: flevible with
	Power circuit: screw clamp terminals 2 12.5 mm ² - cable stiffness: flexible with cable end
	Power circuit: screw clamp terminals 1 14 mm ² - cable stiffness: solid without cable
	end
	Power circuit: screw clamp terminals 2 14 mm ² - cable stiffness: solid without cable
	end Control circuit: screw clamp terminals 1 14 mm ² - cable stiffness: flexible without
	cable end Control circuit: screw clamp terminals 2 14 mm ² - cable stiffness: flexible without
	cable end Control circuit: screw clamp terminals 1 14 mm ² - cable stiffness: flexible with cable
	end
	Control circuit: screw clamp terminals 2 12.5 mm ² - cable stiffness: flexible with cable end
	Control circuit: screw clamp terminals 1 14 mm ² - cable stiffness: solid without
	cable end Control circuit: screw clamp terminals 2 14 mm ² - cable stiffness: solid without
	cable end
Tightening Torque	Power circuit: 1.2 N.m
	Control circuit: 1.2 N.m
Auxiliary Contact Composition	1 NC
	17 V for control circuit
Minimum Switching Voltage	
	5 mA for control circuit
Minimum Switching Current	5 mA for control circuit > 10 MOhm for control circuit
Minimum Switching Voltage Minimum Switching Current Insulation Resistance Non-Overlap Time	

Environment

Standards	IEC 60947-1 IEC 60947-4-1 IEC 60947-5-1
Product Certifications	CE EAC
Ip Degree Of Protection	IP2X conforming to IEC 60529
Protective Treatment	TH (pollution degree 3) conforming to IEC 60068-2-30

Permissible Ambient Air Temperature Around The Device	-2070 °C at Uc -6080 °C storage -555 °C operation
Operating Altitude	3000 m without derating
Fire Resistance	850 °C conforming to IEC 60695-2-1
Mechanical Robustness	Vibrations contactor open (1.5 Gn, 5300 Hz) Vibrations contactor closed (3 Gn, 5300 Hz) Shocks contactor open (7 Gn for 11 ms) Shocks contactor closed (10 Gn for 11 ms)
Height	74 mm
Width	45 mm
Depth	80 mm
Net Weight	0.3 kg

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	8.31 cm
Package 1 Width	7.4 cm
Package 1 Length	4.82 cm
Package 1 Weight	340 g
Unit Type Of Package 2	S02
Number Of Units In Package 2	36
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	12.648 kg

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information