

# เอกสารข้อมูลผลิตภัณฑ์

ข้อมูลจำเพาะ



## LINERGY DP 3P D.BLK/ COMPACT 250A 27HOLES

04033

⚠ เลิกจำหน่ายในวันที่ 15 มิ.ย. 2023

⚠ ยกเลิกแล้ว

### Main

|                                    |                                                                                                                          |
|------------------------------------|--------------------------------------------------------------------------------------------------------------------------|
| Range                              | Linery                                                                                                                   |
| Range Of Product                   | Linery                                                                                                                   |
| Product Or Component Type          | Distribution block                                                                                                       |
| Product Name                       | Linery DP                                                                                                                |
| Range Compatibility                | Prisma Prisma G enclosure<br>Prisma Prisma P enclosure<br>Prisma Prisma PH enclosure<br>Prisma Prisma Pack 250 enclosure |
| Accessory / Separate Part Category | Current distribution accessory                                                                                           |
| Ip Degree Of Protection            | IPxx B                                                                                                                   |

### Complementary

|                  |                                   |
|------------------|-----------------------------------|
| Mounting Support | Prisma mounting plate<br>DIN rail |
|------------------|-----------------------------------|

การสะกดชื่อ: เอกสารนี้ไม่มีวัตถุประสงค์เพื่อใช้แทน หรือใช้เพื่อกำหนดความเหมาะสม หรือความเข้ากันได้ของผลิตภัณฑ์เหล่านี้สำหรับการใช้งานเฉพาะทาง

|                  |                                                                                                                               |
|------------------|-------------------------------------------------------------------------------------------------------------------------------|
| Installed Device | EasyPact: fixed CVS100...160 without earth leakage protection - control: toggle - horizontal installation                     |
|                  | EasyPact: fixed CVS250 without earth leakage protection - control: toggle - horizontal installation                           |
|                  | EasyPact: fixed CVS100...160 without earth leakage protection - control: direct front rotary handle - horizontal installation |
|                  | EasyPact: fixed CVS250 without earth leakage protection - control: direct front rotary handle - horizontal installation       |
|                  | EasyPact: fixed CVS100...160 with earth leakage protection - control: toggle - horizontal installation                        |
|                  | EasyPact: fixed CVS250 with earth leakage protection - control: toggle - horizontal installation                              |
|                  | EasyPact: fixed CVS100...160 with earth leakage protection - control: direct front rotary handle - horizontal installation    |
|                  | EasyPact: fixed CVS250 with earth leakage protection - control: direct front rotary handle - horizontal installation          |
|                  | EasyPact: fixed CVS100...160 without earth leakage protection - control: toggle - vertical installation                       |
|                  | EasyPact: fixed CVS250 without earth leakage protection - control: toggle - vertical installation                             |
|                  | EasyPact: fixed CVS100...160 without earth leakage protection - control: direct front rotary handle - vertical installation   |
|                  | EasyPact: fixed CVS250 without earth leakage protection - control: direct front rotary handle - vertical installation         |
|                  | EasyPact: fixed CVS100...160 with earth leakage protection - control: toggle - vertical installation                          |
|                  | EasyPact: fixed CVS250 with earth leakage protection - control: toggle - vertical installation                                |
|                  | EasyPact: fixed CVS100...160 with earth leakage protection - control: direct front rotary handle - vertical installation      |
|                  | EasyPact: fixed CVS250 with earth leakage protection - control: direct front rotary handle - vertical installation            |
|                  | ComPact: fixed INS250 - control: direct front rotary handle - horizontal installation                                         |
|                  | ComPact: fixed INS250 - control: direct front rotary handle - vertical installation                                           |
|                  | ComPact: fixed INS250 - control: lateral handle - vertical installation                                                       |
|                  | ComPact: fixed INV100 - control: direct front rotary handle - horizontal installation                                         |
|                  | ComPact: fixed INV250 - control: direct front rotary handle - horizontal installation                                         |
|                  | ComPact: fixed INV250 - control: lateral handle - vertical installation                                                       |
|                  | ComPact: fixed INV250 - control: direct front rotary handle - vertical installation                                           |
|                  | ComPact: fixed NSX100...250 and ammeter without earth leakage protection - control: toggle - horizontal installation          |
|                  | ComPact: fixed NSX100...160 without earth leakage protection - control: toggle - horizontal installation                      |
|                  | ComPact: fixed NSX250 without earth leakage protection - control: toggle - horizontal installation                            |
|                  | ComPact: fixed NSX250 with earth leakage protection - control: toggle - horizontal installation                               |
|                  | ComPact: fixed NSX100...160 with earth leakage protection - control: toggle - horizontal installation                         |
|                  | ComPact: fixed NSX100...160 without earth leakage protection - control: direct front rotary handle - horizontal installation  |
|                  | ComPact: fixed NSX250 without earth leakage protection - control: direct front rotary handle - horizontal installation        |
|                  | ComPact: fixed NSX100...160 with earth leakage protection - control: direct front rotary handle - horizontal installation     |
|                  | ComPact: fixed NSX250 with earth leakage protection - control: direct front rotary handle - horizontal installation           |
|                  | ComPact: fixed NSX100...160 without earth leakage protection - control: motor mechanism - horizontal installation             |
|                  | ComPact: fixed NSX250 without earth leakage protection - control: motor mechanism - horizontal installation                   |
|                  | ComPact: plug-in NSX100...160 without earth leakage protection - control: toggle - horizontal installation                    |
|                  | ComPact: plug-in NSX250 without earth leakage protection - control: toggle - horizontal installation                          |
|                  | ComPact: fixed NSX100...160 without earth leakage protection - control: toggle - vertical installation                        |
|                  | ComPact: fixed NSX250 without earth leakage protection - control: toggle - vertical installation                              |
|                  | ComPact: fixed NSX100...160 with earth leakage protection - control: toggle - vertical installation                           |
|                  | ComPact: fixed NSX250 with earth leakage protection - control: toggle - vertical installation                                 |
|                  | ComPact: fixed NSX100...160 without earth leakage protection - control: direct front rotary handle - vertical installation    |
|                  | ComPact: fixed NSX250 without earth leakage protection - control: direct front rotary handle - vertical installation          |
|                  | ComPact: fixed NSX100...160 with earth leakage protection - control: direct front rotary handle - vertical installation       |
|                  | ComPact: fixed NSX250 with earth leakage protection - control: direct front rotary handle - vertical installation             |

---

handle - vertical installation  
ComPact: fixed INV100 - control: direct front rotary handle - vertical installation  
ComPact: fixed INV200 - control: direct front rotary handle - vertical installation  
ComPact: fixed INV160 - control: direct front rotary handle - horizontal installation  
ComPact: fixed INV160 - control: direct front rotary handle - vertical installation  
ComPact: fixed INV200 - control: direct front rotary handle - horizontal installation

|                                          |                                                                                                                                                                                                                                                                                                                                |
|------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Poles Description                        | 3P                                                                                                                                                                                                                                                                                                                             |
| [Ue] Rated Operational Voltage           | 690 V AC                                                                                                                                                                                                                                                                                                                       |
| [Ui] Rated Insulation Voltage            | 750 V AC                                                                                                                                                                                                                                                                                                                       |
| [Uimp] Rated Impulse Withstand Voltage   | 8 kV                                                                                                                                                                                                                                                                                                                           |
| [Ie] Rated Operational Current           | 250 A at 40 °C                                                                                                                                                                                                                                                                                                                 |
| [Icw] Rated Short-Time Withstand Current | 8.5 kA for 1 s                                                                                                                                                                                                                                                                                                                 |
| [Ipk] Rated Peak Withstand Current       | 30 kA                                                                                                                                                                                                                                                                                                                          |
| I²T On Activation                        | 72250000 A².s                                                                                                                                                                                                                                                                                                                  |
| Connections - Terminals                  | Supply: direct connection120 mm²<br>Distribution: spring terminal (per phase) , 6 x 4...10 mm² (flexible)<br>Distribution: spring terminal (per phase) , 3 x 6...16 mm² (flexible)<br>Distribution: spring terminal (per phase) , 6 x 4...10 mm² (rigid)<br>Distribution: spring terminal (per phase) , 3 x 6...16 mm² (rigid) |
| Height                                   | 140 mm                                                                                                                                                                                                                                                                                                                         |
| Width                                    | 105 mm                                                                                                                                                                                                                                                                                                                         |
| Depth                                    | 64 mm                                                                                                                                                                                                                                                                                                                          |
| Net Weight                               | 0.74 kg                                                                                                                                                                                                                                                                                                                        |

## Environment

|                                       |                                                                           |
|---------------------------------------|---------------------------------------------------------------------------|
| Pollution Degree                      | 3                                                                         |
| Overvoltage Category                  | III                                                                       |
| Resistance To Incandescent Wire       | 960 °C conforming to IEC 60695-2-11                                       |
| Standards                             | IEC 60947-7-1<br>IEC 61439-1, inside Prisma<br>IEC 61439-2, inside Prisma |
| Product Certifications                | ASEFA                                                                     |
| Ambient Air Temperature For Operation | -25...55 °C                                                               |

## Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type Of Package 1       | PCE     |
| Number Of Units In Package 1 | 1       |
| Package 1 Height             | 6.5 cm  |
| Package 1 Width              | 12.0 cm |
| Package 1 Length             | 14.5 cm |
| Package 1 Weight             | 720.0 g |
| Unit Type Of Package 2       | BB1     |
| Number Of Units In Package 2 | 10      |
| Package 2 Height             | 12 cm   |
| Package 2 Width              | 24 cm   |
| Package 2 Length             | 34 cm   |
| Package 2 Weight             | 7.25 kg |
| Unit Type Of Package 3       | P06     |
| Number Of Units In Package 3 | 280     |

|                  |          |
|------------------|----------|
| Package 3 Height | 102 cm   |
| Package 3 Width  | 80 cm    |
| Package 3 Length | 60 cm    |
| Package 3 Weight | 207.2 kg |

ความยั่งยืน



ฉลาก **Green Premium™** เป็นความมุ่งมั่นของSchneider Electric ในการส่งมอบผลิตภัณฑ์ที่มีประสิทธิภาพด้านสิ่งแวดล้อมที่ดีที่สุด Green Premium ให้คำมั่นว่าจะปฏิบัติตามกฎระเบียบล่าสุด ความโปร่งใสต่อผลกระทบด้านสิ่งแวดล้อม รวมถึงผลิตภัณฑ์หมุนเวียนและ CO<sub>2</sub> ต่ำ

คู่มือการประเมินความยั่งยืนของผลิตภัณฑ์เป็นเอกสารวิจัยที่ช่วยชี้แจงมาตรฐานฉลากสิ่งแวดล้อมทั่วโลกและวิธีการตีความการประเมิน

[เรียนรู้เพิ่มเติมเกี่ยวกับ Green Premium >](#)

[แนวทางในการประเมินความยั่งยืนของผลิตภัณฑ์ >](#)



ความโปร่งใส RoHS/REACH

ประสิทธิภาพด้านสุขภาพ

- ✓

Reach Free Of Svhc
- ✓

Toxic Heavy Metal Free
- ✓

Mercury Free
- ✓

RoHS Exemption Information

Yes
- ✓

Halogen Free Plastic Parts Product

ใบรับรองและมาตรฐาน

|                          |                                                                                                                             |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Eu RoHS Directive        | Compliant<br><a href="#">EU RoHS Declaration</a>                                                                            |
| China RoHS Regulation    | <a href="#">China RoHS declaration</a><br>Pro-active China RoHS declaration (out of China RoHS legal scope)                 |
| Environmental Disclosure | <a href="#">Product Environmental Profile</a>                                                                               |
| Weee                     | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |